

# Maintenance of Products

All pinta acoustic's foam products are made with open-cell foam. This porous cell structure allows the foam to absorb sound waves. Unless there is a surface coating or covering, it will also absorb water, dust, dirt, oil and other liquids. Normally, very little needs to be done with the products once installed. However, here are some basic instructions for maintaining your pinta acoustic products:

#### **Universal Maintenance Information**

- Always wear white cotton gloves when handling the products.
- Proper supply-and-return air filtration and regular HVAC filter maintenance minimize soiling.

#### **SONEX®** Wall Panels and Baffles

- Do not pressure-wash or soak with water or other liquid.
- Surface dust and dirt can be delicately vacuumed or dusted with air.
- If wall panels and baffles are HPC-coated, lightly wipe clean with damp cloth. Do not soak with water or liquid.

#### **SONEX Clean Baffles and Panels**

- Surface dust and dirt can be delicately vacuumed or dusted with air.
- Gently wipe with a moistened cloth, sponge or brush using water and/or a mild soap or nonabrasive cleaner. Soaps and chemical cleaners need to be approved by pinta acoustic before use. It is important to use clean water throughout the process. Dry the material with a soft towel.

#### **CONTOUR® or HARMONI Ceiling Tiles**

- Do not pressure-wash or soak with water or any other liquid.
- Surface dust and dirt can be delicately vacuumed or dusted with air.
- If ceiling tiles are HPC-coated, lightly wipe clean with damp cloth. Do not soak with water or liquid.

### WHITELINE® Ceiling Tiles

- Do not pressure-wash or soak with water or any other liquid.
- Surface dust and dirt can be delicately vacuumed or dusted with air.

### **SQUARELINE® Metal Ceiling Tiles**

- Do not pressure-wash or soak with water or any other liquid.
- Surface dust and dirt can be delicately vacuumed or dusted with air.
- Metal surface can be spot-cleaned with damp cloth.

#### **SONEX Curtain Enclosures or Materials**

- Do not pressure-wash or soak with water or any other liquid.
- Surface can be wiped with cloth and mild cleaning solution.

## **PROSPEC® Barriers, Foams and Composites**

- Barrier products are extremely dust and dirt resistant and do not require cleaning.
- If barriers are HPC-coated, lightly wipe clean with damp cloth. Do not soak with water or liquid.

For other surface coatings, contact customer service for instructions.



- Wall Panels
- Ceiling Tiles
- Ceiling Clouds
- Baffles
- Barriers, Foam and Composites

2601 49th Avenue North, Suite 400 Minneapolis, MN 55430 1-800-662-0032

+1 612-355-4200

sales@pinta-acoustic.com www.pinta-acoustic.com